SI. No.	Qty.	Description	Rate	Rate in words	Unit	Amount
'		<u>DIVISIONAL OFFICE</u>				
1	20.00	Fully Glazed Partitions			M <sup>2</sup>	
		Slim line partition of approved make :- Supply and installation of full height straight glass partition 12mm thick toughened glass and proprietary electroplated as approved colour with aluminium sections of the SLIM LINE TWIN STYLE TWIN PRO SECTION NO. 6633 (35mm x 25mm) and 6634 (35mm x 20mm) male and female sections providing inside with rubber gaskets in top & bottom upto ceiling level. The glass joints shall be filled with silicon sealant on both side .Rate shall include for providing transport charges, handling, loading and unloading, Installation, protecting the module and glass till handing over, testing, commissioning all necessary hardware's, scafolding, wastage, Structural supports if any, etc. complete and all as per manufacturers specifications as directed. Etching stickers are to be provided as per design. The partition is to be firmly fixed to the floor and ceiling. The partition up to celing only be measured.				
1a	7.00	Fully Glazed Door (Single Shutter)			M <sup>2</sup>	
2	40.00	Providing and fixing fully glazed door of 12 mm thick toughen glass with pencil polish edges alround with etching patterns and bevelled at edges. The door shall be fixed with DORMA patch fitting assembily inclusive of top and bottom patches,pivots, floor spring, bottom locks, SS brushed handle of 60 cm long and 2.5 cm dia. Lock of approved make etc to be fixed to the door, the edge of the glass to be polished			••2	
2	19.00	Counter Partition (120cm (H) )			M <sup>2</sup>	
		The partitions are made of 12 mm thick glass for a height of 45 cm above the solid partition as per the drawing. The bottom portion of the partition is of double skin type for a height of 75 cm. In the frame work verticals and horizontals are made of aluminium section of 50x50x1.2 mm thick of INDAL/JINDAL as internal frame structure placed horizontally & vertically in 60x60 cm				
		Frame work is covered with 9 mm thick marine grade plywood (IS 303) on both sides and finished with 1.0mm thick laminate of approved colour and make.  The partition is firmly fixed to the floor. Necessary wicket doors are to be provided as shown in the drawing .Necessary handles,hinges and tower bolts, auto lock and hydraulic door closer etc. are to be provided for the wicket door.				
3	3.00	Semi partitions Glazed on table top			M <sup>2</sup>	
		Providing and Fixing 10 mm thick toughened glass with machine polished edges shall be fixed with necessary SS brush finish brackets support on wooden partition as per the drawing.				

SI. No.	Qty.	Description	Rate	Rate in words	Unit	Amount
4	54.00	Double Skin Solid Partition			M <sup>2</sup>	
		The partitions are of double skin type. The partition should be firmly fixed on floor/ counter/ wall made out of aluminium section of 50x50x1.2 mm thick of INDAL/JINDAL as internal frame structure placed horizontally & vertically in 60x60 cm interval as shown in the drawing which is covered with 9 mm thick marine grade plywood(IS 303) on both sides and finished with 1 mm thick laminate of approved colour and shade on both sides.				
		The partition is to be firmly fixed to the floor and ceiling.				
4a	2.00	Flush Door in Partitions (One Side Laminated and One Side Painted)			No	
		Providing and fixing 40 mm thick Flush Door using frame work made of 18 mm thick 303 Grade (BWR) Plywood, sandwiched with 6 mm thick 303 Grade (BWR) Plywood. The side facing the Banking Hall shall be finished with 1 mm thick Laminate of approved colour and make and the rear shall be finished with primer, putty and 2 coats of Enamel Paint. Vision Panel of 150 mm width shall be provided using 6 mm thick Plain Glass from 1'-0" upto 6'-0" of the door. The shutter shall be fixed to existing partition frame work using 4 no's of 4" long heavy duty SS hinges. The rates to include mortise lock with SS handle, hinges, stopper, etc.				
4b	0.00	Flush Door in Partitions (Both Side Laminated)			No	
		Providing and fixing 40mm thick Flush Door using frame work made of 18 mm thick 303 Grade (BWR) Plywood, sandwitched with 6 mm thick 303 Grade (BWR) Plywood and both sides finished with 1 mm thick Laminate of aproved colour and make. Vision Panel of 150 mm width shall be provided using 6 mm thick Plain Glass from 1'-0" upto 6'-0" of the door. The shutter shall be fixed to existing partition frame work using 4 no:s of 4" long heavy duty SS hinges. The rates to include mortise lock with SS handle, hinges, stopper, door closer etc.				
5	36.00	Fire Rated Cement Partition			M2	
		The partitions are of double skin type. The partition should be firmly fixed on floor/ counter/ wall made out of GI rectangular section of 44.5x83.5x2.5 mm thick of internal frame structure placed horizontally & vertically in 60x60 cm interval as shown in the drawing which is covered with 6 mm thick fire rated cement board on both sides finished with 2 coat putty and 2 coats of plastic emulsion paint with roller brush of approved colour to match the interior over the approved primer				
5a	2.00	Partly Glazed Door			M2	
		Door is to be provided with Aluminium frame of size 44.5x83.5x2.5 mm alround and intermediates at 60cmc/c and it is covered with 6 mm thick fire rated cement board on both sides and finished with 2 coat putty and 2 coats of plastic emulsion paint with roller brush of approved colour to match the interior over the approved primer				

SI. No.	Qty.	Description	Rate	Rate in words	Unit	Amount
		A 8 mm thick glass is provided at a height of 75cm from bottom.Necessary Fittings such as 4Nos. 125 mm Anodised ball bearing hinges, 1No. godrej lock of approved make, 1 pair of stainless steel handle to each shutter, automatic hydraulic door closer etc. to be provided.				
6	17.00	Roller blind			M2	
		Supplying and providing zebra type roller blinds with smooth operations using manual and clutch roller controlled by a continuous cord loop. The blind is to be fixed within the window opening. The fabric shall be of sun screening quality and of approved shade. Top Roller and bottom roller to be provided with powder coated Aluminium.				
7	1.00	Notice Board			No	
		Providing and fixing notice board of size 120x90x10 cm made of 12 mm thick marine plywood back, 19 mm marine plywood sides, 6 mm thick glass front with locking arrangements. Providing Surge cloth, internal painting and finshing with 1 mm thick laminate (shade and colour as per the instruction by the Architect) etc complete.				
8	1.00	Manager Table With Side Table			No	
		Main Desk Table Top- Made of 25mm thick prelaminated particle board of approved shade confirming to E1 norms. All the edges of workstation surface shall be provided with machine pressed 2mm thick imported PVC lipping glued with hotmelt Eva glue free from any VOC.  Gable End and Modesty - Made of 18mm thick prelaminated particle board of approved shade confirming to E1 norms. All the edges of workstation surface shall be provided with machine pressed 2mm thick imported PVC lipping glued with hotmelt Eva glue free from any VOC.  Size: 160(L) X 75 (W) X 75 (H) Cms Size: 105 (L)x 45 (W) x 75 (H) cms				
9	2.00	Modular Cubicles For CO and U- Manager			No	
		Table Top- Made of 25mm thick prelaminated particle board of approved shade confirming to E1 norms. All the edges of workstation surface shall be provided with machine pressed 2mm thick imported PVC lipping glued with hotmelt Eva glue free from any VOC.  Gable End and Modesty - Made of 18mm thick prelaminated particle board of approved shade confirming to E1 norms. All the edges of workstation surface shall be provided with machine pressed 2mm thick imported PVC lipping glued with hotmelt Eva glue free from any VOC.  SIZE: 150(L) X 75 (W) X 75 (H) Cms  SIDE TABLE: 105 (L)x 45 (W) x 75 (H) cms				

SI. No.	Qty.	Description	Rate	Rate in words	Unit	Amount
10a	5.00	Modular Workstation For Staff - Claims , BA			No	
401	400	Specifications Table Top: 25mm thick Pre laminate particle board with 2mm PVC edge lipping on all exposed edges End Legs: MS powder coated legs 40x40 Intermediate Legs: MS podwer coated 60X40mm legs and supporting MS cross beams (40X20mm) Wire Management 250mm Ht Racway with 65mm Dia Wire Manager Grommet Size: 120 (L) x75 (W) x 75 (H)				
10b	1.00	Linear workstation For Staff			No	
		4 Seater Sharing Workstation 1050x750x750 mm Switch Specifications Table Top: 25mm thick Pre laminate particle board with 2mm PVC edge lipping on all exposed edges End Legs: MS powder coated legs 40x40 Intermediate Legs: MS podwer coated 60X40mm legs and supporting MS cross beams (40X20mm) Wire Management 250mm Ht Racway with 65mm Dia Wire Manager Grommet				
		Size: 105 (L) x75 (W) x 75 (H)				
11	12.00	3 Drawer Pedastal			No	
		Prelam mobile pedestal - 2D+1F with Cylindricle lock Size: 400W X 450D X 600Ht Specifications: Top & Sides: 18mm Thk pre laminated particle board Back: 9mm Thk pre laminated particle board Edge: All exposed area with 2mm thick PVC edge lipping Handle: Finger groove handle Lock: Regular lock				
12	12.00	Keyboard trays			No	
		suppyling and fixing of keyboard trays made of HIP High - Impact -Plastic and mounted under the work top with telescopic sliding channels				
13	1.00	2 Seater sofa			No	
		Two Seater Sofa Pear (Leatheratte / Fabric) 1275L x 725D x700mm H				
14		Back unit				
		Table Top: 18mm Thk pre laminated particle board Back: 9mm Thk pre laminated particle board with 2mm PVC edge lipping Shutters: 18mm Thk pre laminated particle board Edge: All exposed area with 2mm thick PVC edge lipping Handle: Finger groove handle Lock: Regular lock				

SI. No.	Qty.	Description	Rate	Rate in words	Unit	Amount
	1.70	(1) 226(L) X 45(W) X 75 (H) Cms			sqm	
	1.59	(2) 212(L) X 45(W) X 75 (H) Cms			sqm	
	1.61	(3) 215(L) X 45(W) X 75(H) Cms			sqm	
	1.55	(4) 206(L) X 45(W) X 75 (H) Cms			sqm	
	1.46	(5) 195(L) X 45(W) X 75 (H) Cms			sqm	
	3.94	(6) 175(L) X 45(W) X 75 (H) Cms			sqm	
15	3.00	Slotted angle rack			No	
		Supply, Installation , Testing and Commissioning of Slotted angle racks for storage shall be strictly as per the drawings and technical specifications as detailed in the tender and material specificaton shown above . Rate shall include all necessary accessories, hardware components, transportation, installation ,structural components , making good the scratches made during installation etc. as directed by the Engineer in charge  Rack dimensions - 900mm(Length)x375mm(Width)x2400mm(Height)  It will divided in to 8 compartments  (1) 90(L) X 37.5(W) X 240(H) Cms @ Store room				
16	2.00	Modular Table For Agents			No	
		Table Top: 25mm thick Pre laminate particle board with 2mm PVC edge lipping on all exposed edges End Legs: MS powder coated legs 40x40 Modesty Panel: 18mm thk pre lam board with 2mm PVC edge lipping of 450mm Ht Wire Management: Flip up with cable dump  Size: 135 (L) x60 (W) x 75 (H) (5 seats)				
17		CHAIRS				
а	1.00	Manager chair  Amaze Medium Back Mesh Chair * AN 70 Mesh*With Headrest* Self Calibrating Multilock Mechanism* Adjustable Lumbar Support* One Way Adjustable Arms (Height)* Nylon Base * Fabric Upholstered Cushion Seat			No	
b	5.00	Chairs For Agents  Alpha Modium BB (Black) Back Moch Chair* AN 70 Moch* Fixed			No	
		Alpha Medium PP (Black)Back Mesh Chair* AN 70 Mesh* Fixed Arms* Powdercoated 4 Legs* Fabric Upholstered Cushion Seat				
С	11.00	Claims, BA Officers Chair  Comet Medium Back Mesh Chair* AN -70 Mesh* Single Lock Synchro Mechanism* One Way Adjustable Armrests ( Height)*  Nylon Base* Fabric Upholstered Cushion Seat			No	
					ļ	

SI. No.	Qty.	Description	Rate	Rate in words	Unit	Amount
		TP CLAIM HUB		-	-	
1	27.00	Fully Glazed Partitions			M2	
1	27.00	Slim line partition of approved make: Supply and installation of full height straight glass partition 12mm thick toughened glass and proprietary electroplated as approved colour with aluminium sections of the SLIM LINE TWIN STYLE TWIN PRO SECTION NO. 6633 (35mm x 25mm) and 6634 (35mm x 20mm) male and female sections providing inside with rubber gaskets in top & bottom upto ceiling level. The glass joints shall be filled with silicon sealant on both side. Rate shall include for providing transport charges, handling, loading and unloading, Installation, protecting the module and glass till handing over, testing, commissioning all necessary hardware's, scafolding, wastage, Structural supports if any, etc. complete and all as per manufacturers specifications as directed. Etching stickers are to be provided as per design. The partition is to be			M2	
		firmly fixed to the floor and ceiling. The partition up to celing only				
1a	7.00	be measured. Fully Glazed Door (Single Shutter)			M2	
		Providing and fixing fully glazed door of 12 mm thick toughen glass with pencil polish edges alround with etching patterns and bevelled at edges. The door shall be fixed with DORMA patch fitting assembily inclusive of top and bottom patches,pivots, floor spring, bottom locks, SS brushed handle of 60 cm long and 2.5 cm dia . Lock of approved make etc to be fixed to the door, the edge of the glass to be polished				
2	11.00	Counter Partition (120cm (H) )			M2	
		The partitions are made of 12 mm thick glass for a height of 45 cm above the solid partition as per the drawing. The bottom portion of the partition is of double skin type for a height of 75 cm. In the frame work verticals and horizontals are made of aluminium section of $50x50x1.2$ mm thick of INDAL/JINDAL as internal frame structure placed horizontally & vertically in $60x60$ cm  Frame work is covered with 9 mm thick marine grade plywood (IS 303) on both sides and finished with 1.0mm thick laminate of approved colour and make.  The partition is firmly fixed to the floor. Necessary wicket doors				
		are to be provided as shown in the drawing .Necessary handles,hinges and tower bolts, auto lock and hydraulic door closer etc. are to be provided for the wicket door.				
3	1.00	Semi partitions Glazed on table top			M2	
		Providing and Fixing 10 mm thick toughened glass with machine polished edges shall be fixed with necessary SS brush finish brackets support on wooden partition as per the drawing.				

SI. No.	Qty.	Description	Rate	Rate in words	Unit	Amount
4	70.00	Double Skin Solid Partition			M2	
		The partitions are of double skin type. The partition should be firmly fixed on floor/ counter/ wall made out of aluminium section of 50x50x1.2 mm thick of INDAL/JINDAL as internal frame structure placed horizontally & vertically in 60x60 cm interval as shown in the drawing which is covered with 9 mm thick marine grade plywood(IS 303) on both sides and finished with 1 mm thick laminate of approved colour and shade on both sides.  The partition is to be firmly fixed to the floor and ceiling. The partition up to celing only be measured.				
4a	1.00	Flush Door in Partitions (One Side Laminated and One Side Painted)			No	
		Providing and fixing 40 mm thick Flush Door using frame work made of 18 mm thick 303 Grade (BWR) Plywood, sandwiched with 6 mm thick 303 Grade (BWR) Plywood. The side facing the Banking Hall shall be finished with 1 mm thick Laminate of approved colour and make and the rear shall be finished with primer, putty and 2 coats of Enamel Paint. Vision Panel of 150 mm width shall be provided using 6 mm thick Plain Glass from 1'-0" upto 6'-0" of the door. The shutter shall be fixed to existing partition frame work using 4 no's of 4" long heavy duty SS hinges. The rates to include mortise lock with SS handle, hinges, stopper, etc.				
4b	0.00	Flush Door in Partitions (Both Side Laminated)			No	
		Providing and fixing 40mm thick Flush Door using frame work made of 18 mm thick 303 Grade (BWR) Plywood, sandwitched with 6 mm thick 303 Grade (BWR) Plywood and both sides finished with 1 mm thick Laminate of aproved colour and make. Vision Panel of 150 mm width shall be provided using 6 mm thick Plain Glass from 1'-0" upto 6'-0" of the door. The shutter shall be fixed to existing partition frame work using 4 no:s of 4" long heavy duty SS hinges. The rates to include mortise lock with SS handle, hinges, stopper, door closer etc.				
5	0.00	Fire Rated Cement Partition			M2	
		The partitions are of double skin type. The partition should be firmly fixed on floor/ counter/ wall made out of Aluminium rectangular section of 44.5x83.5x2.5 mm thick of internal frame structure placed horizontally & vertically in 60x60 cm interval as shown in the drawing which is covered with 6 mm thick fire rated cement board on both sides finished with 2 coat putty and 2 coats of plastic emulsion paint with roller brush of approved colour to match the interior over the approved primer.  The partition is to be firmly fixed to the floor and ceiling. The partition up to celing only be measured.				

SI. No.	Qty.	Description	Rate	Rate in words	Unit	Amount
5a	0.00	Partly Glazed Door			M2	
		Door is to be provided with Aluminium frame of size 44.5x83.5x2.5 mm alround and intermediates at 60cmc/c and it is covered with 6 mm thick fire rated cement board on both sides and finished with 2 coat putty and 2 coats of plastic emulsion paint with roller brush of approved colour to match the interior over the approved primer				
		A 8 mm thick glass is provided at a height of 75cm from bottom. Necessary Fittings such as 4Nos. 125 mm Anodised ball bearing hinges, 1No. godrej lock of approved make, 1 pair of stainless steel handle to each shutter, automatic hydraulic door closer etc. to be provided.				
6	12.00	Roller blind			M2	
		Supplying and providing zebra type roller blinds with smooth operations using manual and clutch roller controlled by a continuous cord loop. The blind is to be fixed within the window opening. The fabric shall be of sun screening quality and of approved shade. Top Roller and bottom roller to be provided with powder coated Aluminium.				
7	1.00	Notice Board			No	
		Providing and fixing notice board of size 120x90x10 cm made of 12 mm thick marine plywood back, 19 mm marine plywood sides, 6 mm thick glass front with locking arrangements.  Providing Surge cloth, internal painting and finshing with 1 mm thick laminate (shade and colour as per the instruction by the Architect) etc complete.				
8	1.00	Manager Table With Side Table			No	
		Table Top- Made of 25mm thick prelaminated particle board of approved shade confirming to E1 norms. All the edges of workstation surface shall be provided with machine pressed 2mm thick imported PVC lipping glued with hotmelt Eva glue free from any VOC.  Gable End and Modesty - Made of 18mm thick prelaminated particle board of approved shade confirming to E1 norms. All the edges of workstation surface shall be provided with machine pressed 2mm thick imported PVC lipping glued with hotmelt Eva glue free from any VOC.  SIZE: 160(L) X 75 (W) X 75 (H) Cms Size: 105 (L)x 45 (W) x 75 (H) cms				

SI. No.	Qty.	Description	Rate	Rate in words	Unit	Amount
9	7.00	Modular Cubicles			No	
		Table Top- Made of 25mm thick prelaminated particle board of approved shade confirming to E1 norms. All the edges of workstation surface shall be provided with machine pressed 2mm thick imported PVC lipping glued with hotmelt Eva glue free from any VOC.  Gable End and Modesty - Made of 18mm thick prelaminated particle board of approved shade confirming to E1 norms. All the edgesof workstation surface shall be provided with machine pressed 2mm thick imported PVC lipping glued with hotmelt Eva glue freefrom any VOC.				
		SIZE: 150(L) X 75 (W) X 75 (H) Cms SIDE TABLE: 105 (L)x 45 (W) x 75 (H) cms				
10	3.00	Modular Workstation For Staff			No	
10a		Workstation size: 1200X600X750mm  Specifications - Partition system Partition: Height - 1200mm frame with top and sides in Aluminium trims and junctions with diecast caps. Table Top: 25mm thick Pre laminate particle board with 2mm PVC edge lipping on all exposed edges Support: 18mm thick pre laminated gable ends. Wiremanagement: 65mm Grommet cap on table & One metal raceway tile to mount switches below table top level for power and skirting tile for data. Tile Finishes: Above table top Level: Fabric Tiles, one glass marker tile & one magnetic tile per workstation. Below table Top level: Pre-Laminated tiles and metal skirting tile on Main spine towards user.  Size: 120 (L) x60 (W) x 75 (H)				
11	11.00	3 Drawer Pedastal			No	
		Prelam mobile pedestal - 2D+1F with Cylindricle lock Size: 400W X 450D X 600Ht Specifications: Top & Sides: 18mm Thk pre laminated particle board Back: 9mm Thk pre laminated particle board Edge: All exposed area with 2mm thick PVC edge lipping Handle: Finger groove handle Lock: Regular lock				
12	11.00	Keyboard trays			No	
		suppling and fixing of keyboard trays made of HIP High - Impact -Plastic and mounted under the work top with telescopic sliding channels				

SI. No.	Qty.	Description	Rate	Rate in words	Unit	Amount
13	1.00	2 Seater sofa			No	
		Two Seater Sofa Pear (Leatheratte / Fabric) 1275L x 725D				
14		Back unit				
		Table Top: 18mm Thk pre laminated particle board				
		Back: 9mm Thk pre laminated particle board with 2mm PVC				
		edge lipping Shutters: 18mm Thk pre laminated particle board				
		Edge: All exposed area with 2mm thick PVC edge lipping				
		Handle: Finger groove handle				
		Lock: Regular lock				
	1.61	(1) 215(L) X 45(W) X 75(H) Cms			sqm	
	1.01	(2)134(L)x45(W)x75(H)cms			sqm	
	6.75	(3) 150(L) X 45(W) X 75 (H) Cms			•	
15	10.00	Slotted angle rack			sqm No	
13	10.00	Supply, Installation , Testing and Commissioning of Slotted			NU	
		angle racks for storage shall be strictly as per the drawings and				
		technical specifications as detailed in the tender and material				
		specification shown above . Rate shall include all necessary				
		accessories, hardware				
		components,transportation,installation,structural components, making good the scratches made during installation etc. as				
		directed by the Engineer in charge				
		Rack dimensions -				
		900mm(Length)x375mm(Width)x2400mm(Height)				
		It will divided in to 8 compartments				
		(1) 90(L)X37.5(W)X240(H)(Cms)				
16		Modular Table For Agents				
		Table Top: 25mm thick Pre laminate particle board with 2mm				
		PVC edge lipping on all exposed edges Support:				
		End Legs: MS powder coated legs				
		Intermediate Legs: MS podwer coated 60X40mm legs and				
		supporting MS cross beams (40X20mm)				
4=		Size : 135 (L) x60 (W) x 75 (H) (5 seats)				
17	1.00	CHAIRS  Manager shair				
	1.00	Manager chair Amaze Medium Back Mesh Chair * AN 70 Mesh*With Headrest*				
		Self Calibrating Multilock Mechanism* Adjustable Lumbar				
		Support* One Way Adjustable Arms (Height)* Nylon Base *			No	
		Fabric Upholstered Cushion Seat				
	10.00	Officers Chair			No	
		Comet Medium Back Mesh Chair* AN -70 Mesh* Single Lock				
		Synchro Mechanism* One Way Adjustable Armrests ( Height)*				
		Nylon Base* Fabric Upholstered Cushion Seat				
		TOTAL				

SI. No.	Qty.	Description	Rate	Rate in words	Unit	Amount
		COMMON AREA				
1	3.00	Fully Glazed Partitions			M2	
		Slim line partition of approved make :- Supply and installation of full height straight glass partition 12mm thick toughened glass and proprietary electroplated as approved colour with aluminium sections of the SLIM LINE TWIN STYLE TWIN PRO SECTION NO. 6633 (35mm x 25mm) and 6634 (35mm x 20mm) male and female sections providing inside with rubber gaskets in top & bottom upto ceiling level. The glass joints shall be filled with silicon sealant on both side .Rate shall include for providing transport charges, handling, loading and unloading, Installation, protecting the module and glass till handing over, testing, commissioning all necessary hardware's, scafolding,wastage, Structural supports if any, etc. complete and all as per manufacturers specifications as directed. Etching stickers are to be provided as per design. The partition is to be firmly fixed to the floor and ceiling. The partition up to celing only				
1a	5.00	be measured. Fully Glazed Door (Single Shutter)			M2	
		Providing and fixing fully glazed door of 12 mm thick toughen glass with pencil polish edges alround with etching patterns and bevelled at edges. The door shall be fixed with DORMA patch fitting assembily inclusive of top and bottom patches,pivots, floor spring, bottom locks, SS brushed handle of 60 cm long and 2.5 cm dia. Lock of approved make etc to be fixed to the door, the edge of the glass to be polished				
2	0.00	Counter Partition (120cm (H) )			M2	
		The partitions are made of 12 mm thick glass for a height of 45 cm above the solid partition as per the drawing. The bottom portion of the partition is of double skin type for a height of 75 cm. In the frame work verticals and horizontals are made of aluminium section of 50x50x1.2 mm thick of INDAL/JINDAL as internal frame structure placed horizontally & vertically in 60x60 cm  Frame work is covered with 9 mm thick marine grade plywood (IS 303) on both sides and finished with 1.0mm thick laminate of approved colour and make.  The partition is firmly fixed to the floor. Necessary wicket doors are to be provided as shown in the drawing. Necessary				
		are to be provided as shown in the drawing .Necessary handles,hinges and tower bolts, auto lock and hydraulic door closer etc. are to be provided for the wicket door.				
3	0.00	Semi partitions Glazed on table top			M2	
		Providing and Fixing 10 mm thick toughened glass with machine polished edges shall be fixed with necessary SS brush finish brackets support on wooden partition as per the drawing.				

SI. No.	Qty.	Description	Rate	Rate in words	Unit	Amount
4	5.00	Double Skin Solid Partition			M2	
		The partitions are of double skin type. The partition should be firmly fixed on floor/ counter/ wall made out of aluminium section of 50x50x1.2 mm thick of INDAL/JINDAL as internal frame structure placed horizontally & vertically in 60x60 cm interval as shown in the drawing which is covered with 9 mm thick marine grade plywood(IS 303) on both sides and finished with 1 mm thick laminate of approved colour and shade on both sides .				
		The partition is to be firmly fixed to the floor and ceiling. The partition up to celing only be measured.				
4a	0.00	Flush Door in Partitions (One Side Laminated and One Side Painted)			No	
		Providing and fixing 40 mm thick Flush Door using frame work made of 18 mm thick 303 Grade (BWR) Plywood, sandwiched with 6 mm thick 303 Grade (BWR) Plywood. The side facing the Banking Hall shall be finished with 1 mm thick Laminate of approved colour and make and the rear shall be finished with primer, putty and 2 coats of Enamel Paint. Vision Panel of 150 mm width shall be provided using 6 mm thick Plain Glass from 1'-0" upto 6'-0" of the door. The shutter shall be fixed to existing partition frame work using 4 no's of 4" long heavy duty SS hinges. The rates to include mortise lock with SS handle, hinges, stopper, etc.				
4b	2.00	Flush Door in Partitions (Both Side Laminated)			No	
		Providing and fixing 40mm thick Flush Door using frame work made of 18 mm thick 303 Grade (BWR) Plywood, sandwitched with 6 mm thick 303 Grade (BWR) Plywood and both sides finished with 1 mm thick Laminate of aproved colour and make. Vision Panel of 150 mm width shall be provided using 6 mm thick Plain Glass from 1'-0" upto 6'-0" of the door. The shutter shall be fixed to existing partition frame work using 4 no:s of 4" long heavy duty SS hinges. The rates to include mortise lock with SS handle, hinges, stopper, door closer etc.				
5	0.00	Fire Rated Cement Partition			M2	
		The partitions are of double skin type. The partition should be firmly fixed on floor/ counter/ wall made out of Aluminium rectangular section of 44.5x83.5x2.5 mm thick of internal frame structure placed horizontally & vertically in 60x60 cm interval as shown in the drawing which is covered with 6 mm thick fire rated cement board on both sides finished with 2 coat putty and 2 coats of plastic emulsion paint with roller brush of approved colour to match the interior over the approved primer .				

SI. No.	Qty.	Description	Rate	Rate in words	Unit	Amount
5a	0.00	Partly Glazed Door			M2	
		Door is to be provided with Aluminium frame of size 44.5x83.5x2.5 mm alround and intermediates at 60cmc/c and it is covered with 6 mm thick fire rated cement board on both sides and finished with 2 coat putty and 2 coats of plastic emulsion paint with roller brush of approved colour to match the interior over the approved primer  A 8 mm thick glass is provided at a height of 75cm from bottom.Necessary Fittings such as 4Nos. 125 mm Anodised ball bearing hinges, 1No. godrej lock of approved make, 1 pair of stainless steel handle to each shutter, automatic hydraulic door closer etc. to be provided.				
II	1.00	Pantry Room Table			No	
		The size and shape of the table as shown in the drawing. The table is made of 19 mm thick marine plywood and the top of the table is finished with 20mm thick granite top of approved quality and the edges to be rounded and polished. The frame work of the table is with 5x5cm country wood frame fixed on 5x5 cm country wood legs as shown in the drawing .The inner side are painted with 2 coat of enamel paint over a coat of wood primer.				
		TOTAL				

SI. No.	Qty.	Description	Rate	Rate in words	Unit	Amount
		SECOND FLOOR				
1	0.00	Fully Glazed Partitions			M2	
		Slim line partition of approved make :- Supply and installation of full height straight glass partition 12mm thick toughened glass and proprietary electroplated as approved colour with				
2	0.00	Counter Partition (120cm (H) )			M2	
		The partitions are made of 12 mm thick glass for a height of 45 cm above the solid partition as per the drawing. The bottom				
3	0.00	Semi partitions Glazed on table top			M2	
		Providing and Fixing 10 mm thick toughened glass with machine polished edges shall be fixed with necessary SS brush				
4	35.00	Double Skin Solid Partition			M2	
		The partitions are of double skin type. The partition should be firmly fixed on floor/ counter/ wall made out of aluminium section of 50x50x1.2 mm thick of INDAL/JINDAL as internal frame structure placed horizontally & vertically in 60x60 cm interval as shown in the drawing which is covered with 9 mm thick marine grade plywood(IS 303) on both sides and finished with 1 mm thick laminate of approved colour and shade on both sides .				
4a	2.00	Flush Door in Partitions (One Side Laminated and One Side Painted)			NO	
		Providing and fixing 40 mm thick Flush Door using frame work made of 18 mm thick 303 Grade (BWR) Plywood, sandwiched with 6 mm thick 303 Grade (BWR) Plywood. The side facing the Banking Hall shall be finished with 1 mm thick Laminate of approved colour and make and the rear shall be finished with primer, putty and 2 coats of Enamel Paint. Vision Panel of 150 mm width shall be provided using 6 mm thick Plain Glass from 1'-0" upto 6'-0" of the door. The shutter shall be fixed to existing partition frame work using 4 no's of 4" long heavy duty SS hinges. The rates to include mortise lock with SS handle, hinges, stopper, etc.				
4b	0.00	Flush Door in Partitions (Both Side Laminated)			No	
		Providing and fixing 40mm thick Flush Door using frame work made of 18 mm thick 303 Grade (BWR) Plywood, sandwitched with 6 mm thick 303 Grade (BWR) Plywood and both sides finished with 1 mm thick Laminate of aproved colour and make. Vision Panel of 150 mm width shall be provided using 6 mm thick Plain Glass from 1'-0" upto 6'-0" of the door. The shutter shall be fixed to existing partition frame work using 4 no:s of 4" long heavy duty SS hinges. The rates to include mortise lock with SS handle, hinges, stopper, door closer etc.				

SI. No.	Qty.	Description	Rate	Rate in words	Unit	Amount
5	0.00	Fire Rated Cement Partition			M2	
		The partitions are of double skin type. The partition should be firmly fixed on floor/ counter/ wall made out of Aluminium rectangular section of 44.5x83.5x2.5 mm thick of internal frame structure placed horizontally & vertically in 60x60 cm interval as shown in the drawing which is covered with 6 mm thick fire rated cement board on both sides finished with 2 coat putty and 2 coats of plastic emulsion paint with roller brush of approved colour to match the interior over the approved primer				
		The partition is to be firmly fixed to the floor and ceiling. The partition up to celing only be measured.				
5a	0.00	Partly Glazed Door			M2	
		Door is to be provided with Aluminium frame of size 44.5x83.5x2.5 mm alround and intermediates at 60cmc/c and it is covered with 6 mm thick fire rated cement board on both sides and finished with 2 coat putty and 2 coats of plastic emulsion paint with roller brush of approved colour to match the interior over the approved primer				
		A 8 mm thick glass is provided at a height of 75cm from bottom. Necessary Fittings such as 4Nos. 125 mm Anodised ball bearing hinges, 1No. godrej lock of approved make, 1 pair of stainless steel handle to each shutter, automatic hydraulic door closer etc. to be provided.				
6	6.00	Roller blind			M2	
		Supplying and providing zebra type roller blinds with smooth operations using manual and clutch roller controlled by a continuous cord loop. The blind is to be fixed within the window opening. The fabric shall be of sun screening quality and of approved shade. Top Roller and bottom roller to be provided with powder coated Aluminium.				
7	0.00	Notice Board			No	
		Providing and fixing notice board of size 120x90x10 cm made of 12 mm thick marine plywood back, 19 mm marine plywood sides, 6 mm thick glass front with locking arrangements. Providing Surge cloth, internal painting and finshing with 1 mm thick laminate (shade and colour as per the instruction by the Architect) etc complete.				
8	0.00	Manager Table With Side Table			No	
		Table Top- Made of 25mm thick prelaminated particle board of approved shade confirming to E1 norms. All the edges of workstation surface shall be provided with machine pressed 2mm thick imported PVC lipping glued with hotmelt Eva glue free from any				

SI. No.	Qty.	Description	Rate	Rate in words	Unit	Amount
9	0.00	Modular Cubicles			No	
		Table Top- Made of 25mm thick prelaminated particle board of approved shade confirming to E1 norms. All the edges of				
10		Modular Workstation For Staff				
10a	0.00	Size: 120 (L) x60 (W) x 75 (H)			No	
11	0.00	3 Drawer Pedastal			No	
		Prelam mobile pedestal - 2D+1F with Cylindricle lock Size : 400W X 450D X 600Ht				
12	0.00	Keyboard trays			No	
		suppling and fixing of keyboard trays made of HIP High - Impact -Plastic and mounted under the work top with telescopic				
13	0.00	2 Seater sofa			No	
		Two Seater Sofa Pear (Leatheratte / Fabric) 1275L x 725D				
14	0.00	Back unit			sqm	
		Table Top: 18mm Thk pre laminated particle board Back: 9mm Thk pre laminated particle board with 2mm PVC edge lipping Shutters: 18mm Thk pre laminated particle board Edge: All exposed area with 2mm thick PVC edge lipping Handle: Finger groove handle				
15	15.00	Slotted angle rack			No	
		Supply, Installation , Testing and Commissioning of Slotted angle racks for storage shall be strictly as per the drawings and technical specifications as detailed in the tender and material specificaton shown above . Rate shall include all necessary accessories, hardware components,transportation,installation,structural components , making good the scratches made during installation etc. as directed by the Engineer in charge Rack dimensions - It will divided in to 8 compartments (1) 90(L)X37.5(W)X240(H)(Cms)				

SI. No.	Qty.	Description	Rate	Rate in words	Unit	Amount
16	0.00	Modular Table For Agents			No	
		1350x600x750 mm Specifications Table Top: 25mm thick Pre laminate particle board with 2mm PVC edge lipping on all exposed edges End Legs: MS powder coated legs 40x40 Modesty Panel: 18mm thk pre lam board with 2mm PVC edge lipping of 450mm Ht Wire Management: Flip up with cable dum				
17	0.00	CHAIRS			No	
18	0.00	Meeting Room Table-180 (L) x90 (W) x 75 (H)			No	
		1800x900x750mm Specifications Table Top: 25mm thick Pre laminate particle board with 2mm PVC edge lipping on all exposed edges End Legs: MS powder coated legs 40x40 mm Intermediate Legs: MS podwer coated 60X40mm legs and supporting MS cross beams (40X20mm) Wire Management: 450mm Aluminium flipup with soft closure and provision to mount switches and sockets on Cable tray & Intermediate leg with wire entry / vertical wire entry cover considered.				